

NON-AQUEOUS ELECTROLYTIC SECONDARY BATTERY

Publication number: WO03054986

Publication date: 2003-07-03

Inventor: MIYAKE MASAHIDE (JP); FUJIMOTO MASAHISA (JP); KOGA HIDEYUKI (JP); TARUI HISAKI (JP); FUJITANI SHIN (JP)

Applicant: SANYO ELECTRIC CO (JP); MIYAKE MASAHIDE (JP); FUJIMOTO MASAHISA (JP); KOGA HIDEYUKI (JP); TARUI HISAKI (JP); FUJITANI SHIN (JP)

Classification:

- International: H01M4/02; H01M4/38; H01M4/60; H01M4/62; H01M10/36; H01M10/40; H01M4/02; H01M4/36; H01M4/38; H01M4/62; H01M10/36; (IPC1-7): H01M4/02; H01M4/60; H01M4/62; H01M10/40

- European: H01M4/58B; H01M10/0525; H01M10/0561

Application number: WO2002JP13405 20021220

Priority number(s): JP20010389259 20011221; JP20020178142 20020619

Also published as:

US2005019655 (A1)
CN1610980 (A)
AU2002366928 (A1)
CN100370641C (C)


Cited documents:

JP2000228223
US4463072
US4463071
JP3225775
US5554458
more >>

[Report a data error here](#)

Abstract of WO03054986

A non-aqueous electrolytic secondary battery provided with a positive electrode, a negative electrode and a non-aqueous electrolyte, wherein the positive electrode contains sulfur, and the non-aqueous electrolyte contains room-temperature-molten salt having a melting point of up to 60 DEG C.



Data supplied from the esp@cenet database - Worldwide